



CaviBlaster 1030-ROV

Remote Operated Vehicle, 10 gpm & 3,000 psi

Specifications and Options

A compact and powerful submersible hydraulically driven cleaning system compatible with a wide range of Work Class ROVs.

Accessories Included:

Full forward thrust lance.



SKID Dimensions	
Length	20" / 50.8 cm
Width	23-1/4" / 59 cm
Height	9-1/2" / 23.1 cm
Weight	131 Lbs / 54.5 kg

Drive System	
Drive System	Direct Drive
Manufacturer	Permco
Motor	Permco2100-3000
Size Cubic Inches	3.5 CIR
SH Flow - Pressure	22 gpm/84Lpm - 2,160psi/149Bar
AH Flow - Pressure	13gpm/49Lpm - 3,500psi/241Bar

Ideal For
Deep water operations
Piers, Pilings & Seawalls
Running gear & Out drivers
Offshore Operations

Pump System	
Pressure Pump	Udor GSC34/15
Pump Material / Type	SS / Triplex plunger
Flow Rate	10 gpm / 38 Lpm
Nozzle Pressure	3,000 psi / 207 Bar
Hose Diameter	1/2"

Tool
Unbalanced ROV Lance

Shipping Dimensions	
Pallet 30x25x25"	140 Lbs Gross weight



* Pricing and specifications subject to change without notice