



## CaviBlaster 1725-E

Electric Motor of 50 or 60 Hz, 17 gpm & 2,500 psi

### Specifications and Options

This is one of our "Best Seller" units, operating at lower pressures it's designed specifically not to damage paints or coatings yet strong enough to clean to bare metal if needed

### Accessories Included

Feed Hose (15 feet), By-Pass Hose (15 feet),  
High Pressure Hose (50 feet), Zero-Thrust Balanced Gun

### Optional Accessories

Additional pressure hose available in 50 ft or 100 ft sections. (3/4" Diam.)  
Max. Pressure hose length recommended up to 300 ft (100 meters) total



SKID Dimensions	
Length	40" / 102 cm
Width	51" / 140 cm
Height	45" / 114 cm w/wheels
Weight	815 Lbs / 370 kg
Lifting Eyes / FL Slots	YES / YES
Wheels	Yes (optional)

Pump System	
Pressure Pump*	AR RTX70 or RTX60
Pump Material / Type	Brass or Ni Plate / Triplex
Flow Rate	17 GPM
Nozzle Pressure	2,500 PSI
Hose Diam/Max Lgth	3/4" / 600 LF

Shipping Dimensions	
42 x 52 x 50 inches	900 Lbs / 408 kg

Drive System	
Driver	Electric Motor
Enclosure	TEFC
Frame	264T
Hertz	50 or 60 Hz
Voltage*	380V or 208-230V / 460V
Electric Power	3 Phase
Output HP/kW	30 / 22
Speed*	1450 or 1750 RPM
Transmission	Direct Drive
Starting System	Soft Start
Control Box	Nema 4X / IP56

Feed System	
Feed Pump	Centrifugal Self-Prime
Pump Material	Cast Iron
Driver	Electric Motor, 3 Phase
Flow Rate	40 GPM / 152 L / m
Max Lift	20 Lf / 6 M



Tool Options
Zero-Thrust Balanced Gun
Double Un-Balanced Guns
Single CaviDome
ROV Lance

\* Values depend of Hz used

Pricing and specifications subject to change without notice