



CaviBlaster 1222-E

Electric Motor 50/60 Hz, 12 gpm & 2,200 psi

Specifications and Options

This electric version of the 1222-G is compact, lightweight yet provides a superior cleaning performance utilizing the Ultra-Cavitation technology

Accessories Included:

Feed Hose (15 feet), By-Pass Hose (15 feet), Zero-thrust balanced Gun, High Pressure Hose (50 feet)

Optional Accessories:

Additional pressure hose available in 50 ft or 100 ft sections
Max. Pressure hose length recommended up to 300 ft (100 meters) total

SKID Dimensions	
Length w/o handle	35" / 89 cm
Length w handle	45" / 114 cm
Width wheel base	32" / 81 cm
Height	36" / 91 cm
Weight	465 Lbs / 211 Kg

Pump System	
Pressure Pump	General TSF 2421
Pump Material / Type	Brass / Positive Displacement
Flow Rate	12 gpm / 45 Lpm
Pressure	2,200 psi / 152 Bar
Hose Diam/Max Lgth	1/2" - 300 ft / 100 meters

Shipping Dimensions	
Pallet 40x48x36"	565 Lbs Gross weight

* Pricing and specifications subject to change without notice

Drive System	
Motor	Multi-Voltage Electric
Enclosure	TEFC
Frame	284T
Hertz	50 Hz or 60 Hz
Voltage	230-460 V
Phase	3 Phase
Output HP/kW	20 HP / 16 kW
Speed RPM	1,800 RPM
Starting System	Soft Start

Ideal For
Small to Mid size Boat Hulls
Piers, Pilings & Seawalls
Running gear & Out drivers
Pools & Indoor Underwater Instalations

Tool Options
Zero-Thrust Balanced Gun
Double Un-Balanced Guns
Single CaviDome
ROV Lance