

CaviBlaster 0520-E

Electric Motor 60 Hz, 05 gpm & 2,000 psi

Specifications and Options

This electric version of the 0520-G is compact, lightweight yet provides a superior cleaning performance utilizing the Ultra-Cavitation technology

Accessories Included:

Non balanced Gun, High Pressure Hose (50 feet)

Optional Accessories:

Additional pressure hose available in 50 ft or 100 ft sections
Max. Pressure hose length recommended up to 300 ft (100 meters) total



SKID Dimensions

Length w/o handle	27" / 69 cms
Length w handle	33" / 84 cms
Width	22" / 56 cms
Height	21" / 53 cms
Weight	165 Pounds / 75 kgs

Pump System

Pressure Pump	AR RKA 55G30HN
Pump Material / Type	Brass / Positive Displacement
Flow Rate	5 gpm / 19 Lpm
Pressure	2,000 psi / 138 Bar
Hose Diam/Max Lgth	1/2" - 300 ft / 100 meters

Shipping Dimensions

Pallet 40x40x36"	200 Pounds / 91 kgs
------------------	---------------------

Drive System

Motor	Multi-Voltage Electric
Enclosure	TEFC
Frame	H112
Hertz	50 Hz or 60 Hz
Voltage	230-460 V
Phase	3 Phase
Output HP	7.5 HP
Speed RPM USA/Intl.	1,800 / 1,500 RPM
Starting System	Magnetic Start

Ideal For

Small to Mid size Boat Hulls
Piers, Pilings & Seawalls
Running gear & Out drivers
Pools & Indoor Underwater Instalations

Tool Options

Un-Balanced GUN
ROV Lance

* Pricing and specifications subject to change without notice

