



CaviBlaster 2570-E

Electric Motor 50 or 60Hz, 29 gpm & 7,250 psi / 500 BAR

Specifications and Options

This is the ultimate industrial workhorse for serious cleaning or concrete blasting it effectively strips all types of marine fouling and corrosion to bare metal if needed

Accessories Included:

Feed Hose (15 feet), By-Pass Hose (15 feet),
High Pressure Hose (50 feet), Zero-Thrust Balanced Gun

Optional Accessories:

Additional pressure hose available in 50 ft or 100 ft sections. (3/4" Diam.)
Max. Pressure hose length recommended up to 600 ft (200 meters) total



SKID Dimensions	
Length	91" / 200 cm
Width	63" / 139 cm
Height w/eyelifts	58" / 128 cm
Weight	4,800 Lbs / 2,180 kg
Lifting Eyes / FL Slots	YES / YES

Drive System	
Driver	Electric Motor
Model	PEWWE150-18-445T
Motor Enclosure	NEMA-4X / IP56
Frame	445T
Hertz	60 Hz
Voltage	460 Volts
Phase	3 Phase
Output HP/kW	150 HP / 112 kW
Speed RPM	1,800 Rpm
Transmission	Direct Drive
Motor Control	Soft Start
Cont. Box Endo.	WSHD-150N4

Feed System	
Feed Pump	Centrifugal Self-Priming
Lift	20 ft / 6 meter
Flow Rate	62 gpm / 234 Lpm
Power Transm.	Electric Motor

Pump System	
Pressure Pump	Lemasa L150/3
Type	Positive Displacement
Flow Rate	29 gpm / 110 Lpm
Nozzle Pressure	7,250 psi / 500 Bar
Hose Diam/Max Lgth	3/4" - 600 ft - 19 mm / 200 m



Tool Options	
ZT Balanced Gun	
ZT Dump Gun	

Shipping Dimensions	
Pallet 108x72x64"	5,500 Lbs Gross weight



* Pricing and specifications subject to change without notice