



CaviBlaster 2022-E

Electric Motor of 50 or 60 Hz, 20 gpm & 2,200 psi

Specifications and Options

This is our largest commercial unit, operating at lower pressures it's designed specifically not to damage paints or coatings yet strong enough to clean to bare metal if needed

Accessories Included

Feed Hose 15 feet (5 mts), By-Pass Hose 15 feet (5 mts),
High Pressure Hose 50 feet (15 mts), Zero-Thrust Balanced Gun

Optional Accessories

Additional pressure hose available in 50 ft or 100 ft sections. (3/4" Diam.)
Max. Pressure hose length recommended up to 300 ft (100 meters) total



SKID Dimensions	
Length	50" / 127 cm
Width	40" / 101 cm
Height	42" / 107 cm
Weight	1,225 Lbs / 557 kg
Lifting Eyes / FL Slots	YES / YES

Pump System	
Press. Pump (50Hz)	AR-RTX-100.120 N
Press. Pump (60Hz)	AR-RTX-70
Pump Material / Type	SS / Triplex Plunger
Flow Rate	26.4 gpm / 100 Lpm
Nozzle Pressure	2,200 psi / 152 Bar
Hose Diam/Max Lgth	3/4" - 600 ft / 200 m

Shipping Dimensions	
Pallet 52 x 42 x 44"	1,300 Lbs Gross weight

Drive System	
Driver	Electric Motor
Enclosure	TEFC
Frame	264T
Hertz	50 or 60 Hz
Voltage	208-230/460
Phase	3
Output HP/kW	40 / 29.9
Speed @ 50/60Hz	1450/1750 RPM
Transmission	Direct Drive
Starting System	Soft Start
Control Box	Powder Coated Steel

Feed System	
Feed Pump	Self-Priming Centrifugal
Pump Material	Cast Iron
Driver	Electric Motor
Flow Rate	62 GPM / 235 L/m
Max Lift	20 ft / 6 meter



Tool Options	
Zero-Thrust Balanced Gun	
Double Zero-Thrust Balanced Guns	
Single CaviDome	
ROV Lance	

* Pricing and specifications subject to change without notice

CaviDyne LLC, 5077 Fruitville Rd. Suite - 109-157, Sarasota FL, 34232 USA

Phone: (352)275-5319, sales@cavidyne.com, www.cavidyne.com