

## CaviBlaster 0520-E

Electric Motor 50 or 60 Hz, 05 gpm & 2,000 psi

### Specifications and Options

This electric version of the 0520-G is compact, lightweight yet provides a superior cleaning performance utilizing the Ultra-Cavitation technology

#### Accessories Included

Non balanced Gun, High Pressure Hose (50 feet)

#### Optional Accessories

Additional pressure hose available in 50 ft or 100 ft sections. (3/8" Diam.)

Max. Pressure hose length recommended up to 300 ft (100 meters) total



SKID Dimensions	
Length w/o handle	27" / 69 cms
Length w handle	33" / 84 cms
Width	22" / 56 cms
Height	21" / 53 cms
Weight	165 Pounds / 75 kgs

Pump System	
Pressure Pump	AR RKA 55G30HN
Pump Material / Type	Brass / Positive Displacement
Flow Rate	5 gpm / 19 Lpm
Pressure	2,000 psi / 138 Bar
Hose Diam/Max Lgth	3/8" - 300 ft / 100 meters

Shipping Dimensions	
Pallet 40x40x36"	200 Pounds / 91 kgs

Drive System	
Motor	Multi-Voltage Electric
Enclosure	TEFC
Frame	H112
Hertz	50 Hz or 60 Hz
Voltage	230-460 V
Phase	3 Phase
Output HP	7.5 HP
Speed RPM USA/Intl.	1,800 / 1,500 RPM
Starting System	Magnetic Start

Ideal For
Small to Mid size Boat Hulls
Piers, Pilings & Seawalls
Running gear & Out drivers
Pools & Indoor Underwater Instalations



Tool Options
Un-Balanced GUN
ROV Lance

\* Pricing and specifications subject to change without notice