



## CaviBlaster 1725-G

Gasoline Engine, 17 gpm & 2,500 psi

### Specifications and Options

Very popular commercial unit, is a compact and lightweight system with superior cleaning performance utilizing the Ultra-Cavitation technology

#### Accessories Included:

Feed Hose (15 feet) with electric suction pump, By-Pass Hose (15 feet), High Pressure Hose (50 feet), Zero-Thrust Balanced Gun, Battery Start

#### Optional Accessories:

Additional pressure hose available in 50 ft or 100 ft sections, (3/4" Diam Hose)  
Max. Pressure hose length recommended up to 300 ft (100 meters) total



SKID Dimensions	
Length w/o handle	33" / 84 cm
Length w handle	45" / 115 cm
Width	28" / 71 cm
Height	40" / 101 cm
Weight	445 Lbs / 202 Kg

Pump System	
Pressure Pump	AR RTX70
Pump Material / Type	Triplex Plunger – NAB
Flow Rate	17 gpm / 64.5 Lpm
Pressure	2,500 psi / 172 Bar
Hose Diam/Max Lgth	¾" - 300 ft / 100 meters

Shipping Dimensions	
Pallet 40x48x36"	500 Lbs Gross weight

Drive System	
Engine	Kohler ECH980
Engine Type	2-cylinder air-cooled
Intake System	Naturally aspirated
Combustion System	Carburetor with digital CDI
Power Output Max	38 HP / 28 kW
Transmission	Belt Drive
Clutch Type	None
Starting System	Electric

Feed System	
Feed Pump	Johnson Pump L4000
Pump Material	Thermoplastic 12 V Subm.
Flow Rate @ Max Lift	20 gpm/76 L/m at 10'/3m

Ideal For
Small to Mid size Boat Hulls
Piers, Pilings & Seawalls
Running gear & Out drivers
Pools & Indoor Underwater Instalations



Tool Options
Zero-Thrust Balanced Gun
Double Un-Balanced Guns
Single CaviDome
ROV Lance

\* Pricing and specifications subject to change without notice