



CaviBlaster 0520-G

Gasoline Engine with Manual Start, 5 gpm & 2,000 psi

Specifications and Options

Designed as a dependable & durable, yet lightweight and flexible solution for the low budget cleaning operations, the 0520-G has proven to be a great first step into cavitation

Accessories Included:

Unbalanced Diver Gun, High Pressure Hose (50 feet)

Optional Accessories:

Additional pressure hose available in 50 ft or 100 ft sections
Maximum Pressure hose length up to 300 ft (100 meters) total



SKID Dimensions

Length w/o handle	25" / 63 cm
Length w handle	28" / 71 cm
Width wheel base	24" / 61 cm
Height	24" / 61 cm
Weight	95 Lbs / 43 Kg

Pump System

Pressure Pump	Comet ZDWD5030G
Pump Material / Type	Brass / Positive Displacement
Flow Rate	5 gpm @ 3,400 rpm
Nozzle Pressure	2,000psi / 138 Bar
Hose Diam/Max Lgth	3/8" / 300Lft / 100m

Tools

Tool Type	Unbalanced Gun
-----------	----------------

Drive System

Engine	Gas Kohler CH395
Engine Type	4-Stroke OHV
Cooling System	Air
Ignition System	Digital CDI, Variable Timing
Max Output HP/kW	9.5/ 7.1
Clutch	Direct Drive
Starting System	Manual / Recoil

Shipping Dimensions

Pallet 40x48x36"	140 Lbs Gross weight
------------------	----------------------

Ideal For

Small to Mid size Boat Hulls
Piers, Pilings & Seawalls
Running gear & Out drivers
Pools & Indoor Underwater Instalations

* Pricing and specifications subject to change without notice

CaviDyne LLC, 5077 Fruitville Rd. Suite - 109-157, Sarasota FL, 34232 USA

Phone: (352)275-5319, sales@cavidyne.com, www.cavidyne.com



CAVIBLASTER™