

CaviBlaster 4030-E

Electric Motor of 50 or 60 Hz, 40 gpm & 3,000 psi

Specifications and Options

This is an industrial marvel for serious cleaning or concrete blasting it effectively strips all types of marine fouling and corrosion to bare metal if needed



Accessories Included

Feed Hose (15 feet), By-Pass Hose (15 feet), High Pressure Hose (50 feet), Zero-Thrust Balanced Gun

Optional Accessories

Additional pressure hose available in 50 ft or 100 ft sections. (1" Diam.)
Max. Pressure hose length recommended up to 300 ft (100 meters) total



SKID Dimensions	
Length	63" / 160 cm
Width	47" / 119 cm
Height	50" / 127 cm
Weight	2,500 Lbs / 1,136 kg
Lifting Eyes / FL Slots	YES / YES

Pump System	
Pressure Pump	HPP ESR 153/200
Pump Material Type	Coated Cast Iron / Triplex
Flow Rate	40 gpm / 151 Lpm
Nozzle Pressure	2,900 psi / 200 Bar
Hose Diam/Max Lgth	1" - 600 Lft

Shipping Dimensions	
Pallet 48x63x56"	2,650 Lbs Gross weight

Drive System	
Driver	Electric Motor
Enclosure	TEFC
Frame	405T
Hertz	50 / 60 Hz
Voltage	230 / 460 Volts
Phase	3 Phase
Output	100 HP / 75 kW
Speed RPM	1,500 / 1,800 Rpm
Transmission	Direct Drive
Motor Control	Soft Start
Control Box	NEMA 4X / IP 56

Feed System	
Feed Pump	Centrifugal Selfprime
Lift	20 Lft / 6 meter
Flow Rate	62 gpm / 234 Lpm
Driver	Electric Motor



Tool Options	
Zero-Thrust Balanced Gun	

* Pricing and specifications subject to change without notice

CaviDyne LLC, 5077 Fruitville Rd. Suite - 109-157, Sarasota FL, 34232 USA

Phone: (352)275-5319, sales@cavidyne.com, www.cavidyne.com