

## CaviBlaster 1222-E

Electric Motor 50 Hz or 60 Hz, 12 gpm & 2,200 psi

### Specifications and Options

This electric version of the 1222-G is compact, lightweight yet provides a superior cleaning performance utilizing the Ultra-Cavitation technology



#### Accessories Included

Feed Pump with Hose Assembly (15 feet), By-Pass Hose (15 feet), Zero-thrust balanced Gun, High Pressure Hose (50 feet)

#### Optional Accessories

Additional pressure hose available in 50 ft or 100 ft sections. (1/2" Diam.)  
Max. Pressure hose length recommended up to 300 ft (100 meters) total  
Four wheel configuration. Remote control pedal.



| SKID Dimensions   |                  |
|-------------------|------------------|
| Length w/o handle | 35" / 89 cm      |
| Length w handle   | 45" / 114 cm     |
| Width             | 26" / 66 cm      |
| Height            | 29" / 74 cm      |
| Weight            | 465 lbs / 211 Kg |

| Pump System          |                               |
|----------------------|-------------------------------|
| Pressure Pump        | AR XWL 50.20 N                |
| Pump Material / Type | Brass / Positive Displacement |
| Flow Rate            | 13 gpm / 50 Lpm               |
| Pressure             | 2,200 psi / 152 Bar           |
| Hose Diam/Max Lgth   | 1/2" - 300 ft / 100 meters    |

| Shipping Dimensions |                      |
|---------------------|----------------------|
| Pallet 40x48x36"    | 500 lbs Gross weight |

| Drive System        |                        |
|---------------------|------------------------|
| Motor               | Multi-Voltage Electric |
| Enclosure           | TEFC                   |
| Frame               | 284T                   |
| Hertz               | 60 Hz                  |
| Voltage             | 230-460 V              |
| Phase               | 3 Phase                |
| Output HP/kW        | 20 HP / 16 kW          |
| Speed RPM USA/Intl. | 1,800 / 1,500 RPM      |
| Starting System     | Magnetic Start         |

| Feed System       |                           |
|-------------------|---------------------------|
| Feed Pump         | Johnson L2200             |
| Pump Material     | Thermoplastic, SS Shaft   |
| Flow Rate         | 29 gpm/110L/m @ 3.3Lft/1m |
| Pump Power Supply | 12V @ 7.5 Amp             |

| Ideal For                              |
|--|
| Small to Mid size Boat Hulls           |
| Piers, Pilings & Seawalls              |
| Running gear & Out drivers             |
| Pools & Indoor Underwater Instalations |



| Options                  |
|--------------------------|
| Zero-Thrust Balanced Gun |
| Double Un-Balanced Guns  |
| Single CaviDome          |
| ROV Lance                |
| 4 Wheels                 |
| Remote Foot Pedal        |

\* Pricing and specifications subject to change without notice

CaviDyne LLC, 5077 Fruitville Rd. Suite - 109-157, Sarasota FL, 34232 USA

Phone: (352)275-5319, sales@cavidyne.com, www.cavidyne.com