



Zero Thrust Balanced Lance

Specifications and Options

This cutting-edge industrial innovation represents a formidable solution for the meticulous task of thorough cleaning. It excels in efficiently removing various forms of marine fouling, while preserving the integrity of protective coatings. This versatile lance can be precisely configured to accommodate a spectrum of operational requirements, offering tailored thrust configurations such as 100% frontal thrust, 70-30, and 50-50 ratios. These adjustments cater to the distinct demands encountered by individual Remotely Operated Vehicles (ROVs).

Optional Accessories:

10 feet of 1/2" hose up to 6,000 psi. T-Bracket

Lance Dimensions	
Material	Stainless Steel
Wall Thickness	0.154" (Schedule 80)
Diameter	1-1/8" / 2.86 cm
Length	20.08" / 51 cm
Inlet	1/2" NPT
Weight	3.4 Lbs / 1.54 Kgs

Ideal for CaviBlasters	
2540-D	2540-E
1725-G	1725-E
1625-D	1625-E
1228-G	1222-E

** Also compatible with ROV CaviBlasters*

Shipping Dimensions	
Box 25x4x4 inches	7 Lbs / 3.20 Kgs

** Pricing and specifications subject to change without notice*

CaviDyne LLC, 5077 Fruitville Rd. Suite - 109-157, Sarasota FL, 34232 USA
Phone: (941) 413-5431, sales@cavidyne.com, www.cavidyne.com

