

CaviBlaster 1325-D

Diesel Engine, 13 GPM & 2,500 PSI



Specifications and Options

A compact EPA compliant Tier-4F diesel has recently become available, filling the need for a mid-sized, diesel-powered commercial CaviBlaster. Rated at 13 GPM / 2,500 PSI, the CaviBlaster Model 1325-D now offers a rugged diesel version.

Accessories Included:

Feed Hose (15 feet), By-Pass Hose (15 feet),
High Pressure Hose (50 feet), Zero-Thrust Balanced Gun, Battery Start

Optional Accessories:

Additional pressure hose available in 50 ft or 100 ft sections (1/2" Diam.)
Max. Pressure hose length recommended up to 300 ft (100 meters) total



SKID Dimensions	
Length	56" / 142 cm
Width	37" / 94 cm
Height	42" / 106 cm
Weight	700 lbs / 320 kg
Fuel Containment Pan	YES
Lifting Eyes	YES

Pump System	
Pressure Pump	Udor CKC 50 / 15 S
Pump Material / Type	Triplex Plunger / NAB
Flow Rate	13.2 GPM / 50 L/m
Nozzle Pressure	2,500 PSI / 172 BAR
Hose Diam/Max Lgth	1/2" 300 Lft -12.5 mm / 100 m

Shipping Dimensions	
Pallet 56 x 40 x 44"	750 lbs Gross weight

Drive System	
Engine	Yanmar 3TNV82
EPA regulation	USA Tier-4 / EU Stage IV
Engine Type	3-Cylinder - 4-Cycle
Cooling System	Liquid with Axial Fan
Combustion System	IDI Naturally Aspirated
Exhaust	Muffler
Output Intern. HP/kW	23.7 HP / 17.7 kW
Transmission	Direct, Reduction Gearbox
Starting System	Electric Starter
Emergency Shut-off	Yes

***PRICING AND SPECIFICATIONS SUBJECT TO
CHANGE WITHOUT NOTICE**

Feed System	
Feed Pump	Johnson L2200
Pump Material	Thermoplastic, SS Shaft, Bilge
Flow Rate	33 GPM / 125 l/m @ 3 Lft / 1 m
Drive	12V / 7.5 Amp Electric



Tool Options
Zero-Thrust Balanced Gun
Double UnBalanced Guns
Single CaviDome
ROV Lance